



TUBING ASSEMBLY OPTIONS

GeoPump offers a variety of tubing options in twin bonded configurations. Material options of polyethylene, Teflon® lined polyethylene, or pure Teflon® provide economy and chemical inertness. Bonded tubing eliminates the potential of interference with portable static water level measurement probes.

MODEL #	STYLE	MATERIAL	AIR TUBE I.D. X O.D. (IN/CM)	WATER TUBE I.D. X I.D. (IN/CM)	COMPATIBLE PUMP
5688	Bonded Twin	Polyethylene	.375 x .500/ 0.95 x 1.27	.625 x .750/ 1.59 x 1.91	5662 5952
5689	Bonded Twin	Polyethylene	.375 x .500/ 0.95 x 1.27	.375 x .500/ 0.95 x 1.27	5972 5973 5974 5975
5740	Bonded Twin	Teflon Lined Polyethylene	.250 x .375/ 0.64 x 0.95	.500 x .625/ 1.27 x 1.59	57000M 57100M 57200M 57300M
5741	Bonded Twin	Polyethylene	.250 x .375/ 0.64 x 0.95	.500 x .625/ 1.27 x 1.59	57000M 57100M 57200M 57300M
5856	Bonded Twin	Polyethylene	.170 x .250/ 0.43 x 0.64	.170 x .250/ 0.43 x 0.64	57400 57500
5857	Bonded Twin	Teflon Lined Polyethylene	.170 x .250/ 0.43 x 0.64	.170 x .250/ 0.43 x 0.64	57400 57500
5896	Bonded Twin	Polyethylene	.250 x .375/ 0.64 x 0.95	.375 x .500/ 0.95 x 1.27	57000 5615 5635 57200 5625
5897	Bonded Twin	Teflon Lined Polyethylene	.250 x .375/ 0.64 x 0.95	.375 x .500/ 0.95 x 1.27	57000 5615 5635 57200 5625
5906	Bonded Twin	Polyethylene	.170 x .250/ 0.43 x 0.64	.250 x .375/ 0.64 x 0.95	57400 57500
5907	Bonded Twin	Teflon Lined Polyethylene	.170 x .250/ 0.43 x 0.64	.250 x .375/ 0.64 x 0.95	57400 57500

Note: Teflon is a registered trademark of E.I. duPont.

• **GeoPump, Inc.** • 213 State Street • Medina, NY 14103 • www.geopump.com •
 • Toll Free 877-Geo-Pump • 585-798-6666 Outside USA • 585-798-0175 Fax •